

6 W 5" ceiling loudspeaker EN 54, metal



Part-No. 582407

Approval as per EN 54-24, 1438/CPD/0233

With its flat form, the type DL-E 06-130/T-EN 54-24 recessed ceiling loudspeaker is optically a good fit for the ceilings for which they were designed. The 5" broadband loudspeaker chassis, which is impregnated against humidity, distinguishes itself by way of its high degree of effectiveness. Typically, the 6 W, 3 W, or 1.5 W adjustment is done to the loudspeaker. The spring latch (2 pieces) guarantees uncomplicated and quick mounting onto the ceiling. In the standard version, a protective cover made out of a synthetic material is mounted to the back side of the loudspeaker, but a fire dome certified according to the EN 54-24 standard is optionally available as well. If the loudspeaker is also meant to be used in accordance with BS 5839-8, it is possible to include the optional thermal fuse and a ceramic connecting terminal with the order, and to mount them.

Ambient temperature	-10 °C ... 55 °C
Rated Power	6 W
Transformer power taps	6/3/1.5 W
Color	white, similar to RAL 9010
Weight	approx. 0.75 kg
Dimensions	Ø: 181.5 mm D: 59 mm

Accessories:

Optional:

582407.FD Fire dome (FE 130.1) for ceiling loudspeaker Part No. 582407, 582407. SAFE