

## Extinguishing panel 8010, Series 4, w/o operating unit



### Part-No. 788012.40

Corresponding indication and operating panel available in different languages, which can be found in "Options for Extinguishing Control Panels 8010 Wall Mounting".

#### Features:

- 1 Extinguishing area for max. 1,600 m<sup>2</sup> acc. to VdS
- 8 detector zones for up to 30 series 9200 and IQ8Quad automatic detectors each (for two-detector dependency up to 25 detectors)
- 1 zone for manual alarm
- 1 zone for emergency stop
- 1 zone for post flooding
- 1 zone for extinguishing system fault
- 1 zone for blocking extinguishing system
- 1 control input for buzzer OFF
- 1 control input for control panel reset
- 8 relays, monitored or floating 30V DC/2A
- 3 relays, floating 30V DC/2A
- 2 mains voltage relays, floating 230V AC/2A
- All outputs are provided with fuses

Rated voltage	230 V AC
Rated frequency	50 ... 60 Hz
Rated current	0.7 A
Operating voltage	24 V DC
Quiescent current	approx. 100 mA
Battery capacity	2 x 12 V/24 Ah
Ambient temperature	-5 °C ... 45 °C
Storage temperature	-10 °C ... 50 °C
Type of protection	IP 30
Class of protection	I
Housing	sheet steel approx. 1.25 mm
Air humidity	< 95 % non condensing
Color	gray (similar to RAL 7035), blue (similar to RAL 5003)
Weight	approx. 18.3 kg (without battery)
Dimensions	W: 488 mm H: 625 mm D: 210 mm

#### Accessories:

- 788400 display and control panel for LMST 8010, DE
- 788401 display and control panel for LMST 8010, GB