

Conventional MCP compact, small, red, glass pane



Part-No. 804970

Approval: VdS, CNBOP

Including housing and alarm indicator. For connection to a conventional detection zone.

Operating voltage	8 ... 30 V DC
Alarm current @ 9 V DC	9 mA
Alarm display	red LED and yellow actuation indicator
No. of detector/zone	10 detectors per zone (according to VdS)
Application temperature	-20 °C ... 70 °C
Storage temperature	-30 °C ... 75 °C
Connection terminal	max. 2.5 mm ² (AWG 26-14)
Type of protection	IP 43, IP 55 with 704965
Housing	PC ASA plastic
Air humidity	< 95 % (non condensing)
Color	red, similar to RAL 3020
Weight	approx. 110 g
Detector specification	EN 54-11, type A
Dimensions	W: 88 mm H: 88 mm D: 21 mm

Features:

- Slimline design
- Low power consumption
- Plug-in connection terminals (two direction)
- Optional terminal terminals
- Triple key function (test, open, reset)
- Detectors that are not ready for operation can be marked with the "Out of order" label by reversing the enclosed glass pane



If the glass pane is replaced with the optionally available plastic pane with reset function, the MCP can be reset from the outside using the key.

For the surface mounting of the MCP the surface mount base Part No. 704980 must be ordered separately, if the cable wasn't laid about a standard flush mount wall socket.

Type a definition - single action in accordance with EN 54-11 § 3.4.1

(excerpt taken from EN standard):

Manual fire alarm unit, for which the alarm status is automatically set (additional alarm triggering is not required) after the fragile element has been broken or its position has been changed.



1 x Glass pane 704960

1 x Key 704966

1 x Multilingual paper labels with "Out of order" pictogram.

Accessories:

704980 Surface mount housing