



The performance features at a glance

- Energie saving LED Technology
- 23.6"
- Max Resolution 1920 x 1080
- Aspect ratio 16:9
- VESA 100mm x 100mm
- BNC, HDMI, VGA inputs
- Screen protection

High versatility

Compact and yet sufficiently large: the LME23.6SP impresses with its very balanced image quality. Thanks to the 16:9 this is especially suited for the recorder of the pixel master (GXi) series and the DigiMaster FX.

Outstanding advantages

Numerous inputs allow you to connect various devices to these monitors. Besides two BNC slots, you also have a VGA and a HDMI slot available.

Furthermore, you can feed in audio signals via PC Stereo or RCA (cinch) and make them audible via the integrated loud speakers.

High-performance technology

The maximum resolution is 1920 x 1080 with an aspect ratio of 16:9. A relatively strong luminosity of 300cd/sq m produces clear images even in a bright environment.

Additional special features

Functions such as PIP or POP ensure greater transparency. The scope of delivery includes the desktop base, a VGA cable as well as a power supply unit. In addition, the screen surface is protected by a sheet of plexiglass.

Order data

Order number	Product description
LME23.6SP	LED TFT, max. 1920x1080 @60Hz, 5ms, image format 16:9, PAL/NTSC, built-in loudspeakers, 12VDC, VESA 100x100mm, with desktop base / remote control / vga cable, screen protection

LME23.6SP LED-Monitor



Advantages for the installer

Compact dimensions, low weight, and a clear OSD menu provide for simple commissioning. Furthermore, each model is equipped with a VESA connection (100mm x 100mm).



Technical specifications	LME23.6SP
Video standard	PAL / NTSC
Screen size	23.6"
Resolution	1920 x 1080
Aspect ratio	16:9
Displayable colours	16.7 M
Response time	5 ms
Angle of view (L/R)	80° / 85°
Luminosity	300 cd/m ²
Contrast range	5000 : 1
Operating hours (MTBF)	2x BNC, VGA, HDMI
Video inputs	2x BNC
Video outputs	PC Stereo, RCA
Audio inputs	RCA
Loudspeaker output	2x 1,5 Watt
OSD Menu	English, German, French, Italian, Spanish, Russian, Turkish, Polish, Dutch, Czech
3D Comb Filter / De-Interlace	Yes / Yes
PIP / POP	Yes / Yes
VESA connection	100mm x 100mm
Voltage supply	12 VDC (Power supply 230V)
Voltage supply Power consumption	33 Watt
Operating temperature	0°C - 40°C
Dimensions	580mm x 428mm x 164mm
Weight	3,2 kg