

13ZD Series Motorized Zoom Lens

1/3-INCH FORMAT, AUTO IRIS (DIRECT DRIVE)

Product Features

- CS Mount
- Spot Filter
- For Use with 1/3-Inch Format Cameras
- Auto Iris (Direct Drive, No Amplifier), Motorized Focus and Zoom (with or without Presets)
- High Resolution Power in Compact Body



13ZD5.6X20


Pelco's **13ZD Series** of 1/3-inch motorized zoom lenses cover a wide range of applications from wide angle to telephoto. Each auto iris lens in this series covers a specific range of focal lengths and is available with or without preset positioning.

Appropriate for indoor and outdoor lighting situations, the **13ZD Series** lenses will fit all 1/3-inch CS-mount cameras requiring DC-drive auto iris lenses. In addition, all auto iris lenses include a spot filter. A factory-installed, square 4-pin auto iris connector is standard.

Lenses in this series are available in 8X, 10X, 15X, 20X, and 30X zoom with varying focal lengths.

Maximum apertures of f/1.6 or f/1.8 and a minimum aperture of f/360 allow excellent performance characteristics across a wide range of lighting conditions.

NOTE: VALUES IN PARENTHESES ARE INCHES; ALL OTHERS ARE CENTIMETERS.



MODEL	H	W	L
13ZD6X8	8.00 (3.15)	6.93 (2.73)	12.12 (4.77)
13ZD6X10(P)	8.00 (3.15)	6.93 (2.73)	12.12 (4.77)
13ZD6X15P	8.00 (3.15)	6.93 (2.73)	12.12 (4.77)
13ZD5.6X20(P)	8.00 (3.15)	6.93 (2.73)	12.29 (4.84)
13ZD5.5X30(P)	8.00 (3.15)	8.71 (3.43)	16.69 (6.57)

NOTE: MEASUREMENTS ARE WITH LENSES FULLY EXTENDED (FOCUS-NEAR MODE).

TECHNICAL SPECIFICATIONS

MODELS

	13ZD6X8	13ZD6X10/ 13ZD6X10P	13ZD6X15P
Type	Motorized Zoom	Motorized Zoom	Motorized Zoom
Format Size	1/3-inch	1/3-inch	1/3-inch
Mount Type	CS	CS	CS
Focal Length	6 ~ 48 mm	6 ~ 60 mm	6 ~ 90 mm
Zoom Ratio	8X	10X	15X
Relative Aperture (f)	1.6 ~ 360	1.6 ~ 360	1.6 ~ 360
Operation			
Iris	Auto (Direct Drive)	Auto (Direct Drive)	Auto (Direct Drive)
Focus	Motorized*	Motorized*	Motorized*
Zoom	Motorized*	Motorized*	Motorized*
Angle of View			
Diagonal	7.3° ~ 54.4°	5.8° ~ 54.3°	3.9° ~ 54.3°
Horizontal	5.8° ~ 44.2°	4.7° ~ 44.2°	3.1° ~ 44.2°
Vertical	4.4° ~ 33.5°	3.5° ~ 33.5°	2.4° ~ 33.5°
Minimum Object Distance	1.0 m	1.0 m	1.0 m
Back Focal Length	10.10 mm	9.55 mm	9.55 mm
Filter Size (mm)	46P0.75	55P0.75	55P0.75
Unit Weight	0.42 kg (0.92 lb)	0.54 kg (1.19 lb)	0.65 kg (1.43 lb)
Shipping Weight	0.90 kg (2.0 lb)	1.36 kg (3.0 lb)	1.36 kg (3.0 lb)
	13ZD5.6X20/ 13ZD5.6X20P	13ZD5.5X30/ 13ZD5.5X30P	
Type	Motorized Zoom	Motorized Zoom	
Format Size	1/3-inch	1/3-inch	
Mount Type	CS	CS	
Focal Length	5.6 ~ 112 mm	5.5 ~ 165 mm	
Zoom Ratio	20X	30X	
Relative Aperture (f)	1.6 ~ 360	1.8 ~ 360	
Operation			
Iris	Auto (Direct Drive)	Auto (Direct Drive)	
Focus	Motorized*	Motorized*	
Zoom	Motorized*	Motorized*	
Angle of View			
Diagonal	3.2° ~ 59.4°	2.1° ~ 58.7°	
Horizontal	2.6° ~ 47.6°	1.7° ~ 47.6°	
Vertical	1.9° ~ 35.7°	1.3° ~ 33.9°	
Minimum Object Distance	1.5 m	1.8 m	
Back Focal Length	8.97 mm	15.5 mm	
Filter Size (mm)	55P0.75	72P0.75	
Unit Weight	0.56 kg (1.23 lb)	0.83 kg (1.84 lb)	
Shipping Weight	1.36 kg (3.0 lb)	1.36 kg (3.0 lb)	

*Model numbers with P suffix are motorized with preset capability.

CERTIFICATIONS

- CE, Class B (all models)
- C-Tick

Pelco by Schneider Electric

3500 Pelco Way, Clovis, California 93612-5699 United States

USA & Canada Tel (800) 289-9100 Fax (800) 289-9150

International Tel +1 (559) 292-1981 Fax +1 (559) 348-1120

www.pelco.com

Pelco, the Pelco logo, and other trademarks associated with Pelco products referred to in this publication are trademarks of Pelco, Inc. or its affiliates. All other product names and services are the property of their respective companies. Product specifications and availability are subject to change without notice.

©Copyright 2011, Pelco, Inc. All rights reserved.